













Illustrative picture

SPECIFICS

<i>Description</i>	Product type	Anti-crushing plug in rubber 10A 2P+E 250V S11
	Article code	RS78003
	Commercial Series	ANTI-CRUSHING SERIES

<i>General Data</i>	Poles	N° 2P+E	Type of material	/					
	Current	A 10	Dimensional stability	°C -25 /+70					
	Voltage	V~ 250	Resistance glow wire test	°C +650 / +750					
	Degree of protection	IP 20	Working temperature	°C , -15 + 35					
	Impact Resistance	IK 8	Weight	kg 0,024					
	Insulation Resistance	MΩ >10							
	Dimensions LxDxH	cm 8,2x3,2x1,5							
	Behaviour with chemical and atmospheric agents								
	Acids		Bases		Solvents			Mineral Oil	UV rays
Saline Solution	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol	
Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Limited Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 

<i>Standards</i>	CEI 23-50	2011/65/UE
------------------	-----------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,024
	Package innerbox		90	2,25
	Packaging		720	18,62



Rev	Date	Technical Manager
01	7/1/20	Romano Rosi